



K.B.K. fire
protipožární ochrana



Textile roll-up fire shutter FIROTEX - V is one of fire shutters that is used for the separation of two fire sections. The fire roll-up shutter is open under regular conditions (rolled up) and rolls down automatically only in the event of fire by the impulse from the electric fire signalization system or possibly any similar sensitive detection system. Sytem FIROTEX - V is certified by Approved body PAVUS, a.s. and FIRES Ltd for the use in the CR and Slovakia.

FIROTEX - V

Fire roll-up shutter is tested in accordance with requirement under ČSN EN 14 600 in connection to tests of fire resistance under ČSN EN 1634 - 1 and consecutive norms. Fire roll-up shutter FIROTEX - V has a declared fire resistance under ČSN EN 13 501 - 2:

- EW 15 DP1-C1
- EW 30 DP1-C1

It is possible to reach fire resistance EW 45 DP1-C1 to EW 120 DP1-C1 or EI 15 DP1-C1 to EI 120 DP1-C1 by means of a water sprinkling system..

The load bearing structures of the shutter are made of steel metal sheets. The filling of the opening comprises of a special textile that is wound on a steel tubular shaft which is fitted with a tubular electric motor. The surface finish of visible elements except for the special textile itself may be done in the colour range according to the requirements from the customer (RAL).



K.B.K. fire, s.r.o.
Heydukova 1093/26
702 00 Ostrava-Průvoz
tel.: +420 553 810 560
obchod@kbkfire.cz